NUELLER

Used milk cooling tank Model O-92

The Mueller tank is exclusively made of AISI 304 quality stainless steel (DIN-1.4301) and complies with the ISO 5708 standard for milk cooling tanks. In addition, the tank is superbly made (welded seamless) and polished. The heavy beam profile and adjustable legs ensure a uniform weight distribution, so that the tank can be placed in almost every bulk milk tank room. A fixed solid stainless ladder is fitted to the tank from model O-700 upwards.



The O-92 model includes the following features:

- Cleaning water level control.
- Deep-cool switch.
- Automatic cool start.
- Digital temperature indication.
- Fitted ladder from model O-700 upwards.
- Dipstick.
- Calibration card.

CIRCULATION CLEANING SYSTEM (CRS)



The circulation cleaning system was developed in the early 1990s. This fully-automated cleaning system (based on circulation cleaning) is mounted on the front side of the O-model.

QUICK CLEANING SYSTEM (VRS)





The cleaning system was further developed into a quick-wash cleaning system at the end of the 1990s. This quick wash or displacement cleaning system has major advantages compared to the circulation cleaning system:


- more economical (about 35% water saving).
- quicker (about 50% less cleaning time).
- environmentally friendly (less water and electricity consumption).

Mueller Sales









Dimension (mm)

Model	Maximum capacity in Litres	Length (B)	Width (C)	Height (A) incl. Spray Pipe horizontally measured	Height (A1) incl. agitator horizontally measured
OC 400	1.725	2020	1530	1250	1530
O 450	1.900	2165	1530	1250	1530
O 500	2.125	2370	1530	1250	1530
O 600	2.530	2725	1530	1250	1530
0 700	2.960	2340	1790	1450	1790
O 800	3.300	2550	1790	1450	1790
O 900	3.700	2800	1790	1450	1800
O 1000	4.105	3050	1790	1450	1800
0 1125	4.580	3350	1790	1450	1810
O 1250	5.085	2930	2020	1700	1900
O 1500	6.150	3435	2020	1700	1910
0 1750	7.130	3915	2020	1700	1920
O 2000	8.180	4430	2020	1700	1930
OC 2000	8.100	3435	2270	1900	2150
O 2250	9.120	3815	2270	1900	2160
O 2500	10.020	4150	2270	1890	2170
O 2750	11.050	4530	2270	1890	2180
O 3000	12.000	4880	2270	1890	2210
O 3500	13.800	4880	2450	2000	2280
O 4000	15.670	5490	2450	2000	2320
O 4500	18.750	4910	2800	2300	2605
O 5000	20.560	5340	2800	2300	2605
O 6000	24.020	5605	3010	2430	2650
O 7000	28.200	5605	3210	2670	2850
O 8000	32.700	5605	3410	2890	3015

Length incl. Quick cleaning system (VRS) is +50 mm.

Mueller Sales

Narcisstraat 14 P.O.Box 138 9400 AC Assen The Netherlands T: +31 (0)592 361 600 F: +31 (0)592 361 601 E: info@muellerbv.com Your Mueller dealer:

www.muellerbv.com

GMO-EN-12-09

It is possible that some of the information in this folder may deviate from the actual execution. Consequently, no rights may be reserved with respect to the information contained in this folder. Mueller has a policy of continuous product development and reserves the right to change or modify any product and specification without prior notice.