




使用说明:

工作方式: S1
绝缘等级: B级 F级
环境温度: -30°C ~ 60°C

应用范围:

4D-500 380V/50Hz 0-90Pa (20Pa-6300m³/h)
4E-500 220V/50Hz 0-90Pa (20Pa-6000m³/h)
6D-500 380V/50Hz 0-90Pa (20Pa-4350m³/h)
6E-500 220V/50Hz 0-90Pa (20Pa-4400m³/h)



			VOLTAGE 额定电压	FREQUENCY 频率	CURRENT 额定电流	INPUT 输入功率	SPEED 额定转速	AIR VOLUME 额定风量	CAPACITANCE 电容	NOISE 噪音	NET WEIGHT 净重	LICENSE 证书	NO. ON THE CURVE
YWF-4D-500-S-137/35-G	YWF-4D-500-S-137/35-T	YWF-4D-500-S-137/35-B	380	50	0.9	450	1300	6570	/	72	9.0		
YWF-4E-500-S-137/35-G	YWF-4E-500-S-137/35-T	YWF-4E-500-S-137/35-B	220	50	1.95	420	1300	6420	10	72	9.0		
YWF-6D-500-S-137/35-G	YWF-6D-500-S-137/35-T	YWF-6D-500-S-137/35-B	380	50	0.55	230	900	4840	/	68	9.0		
YWF-6E-500-S-137/35-G	YWF-6E-500-S-137/35-T	YWF-6E-500-S-137/35-B	220	50	1.15	230	900	4830	10	68	9.0		

