




使用说明:

工作方式: S1
绝缘等级: B级 F级
环境温度: -30°C ~ 60°C

应用范围:

4D-350 380V/50Hz 0~90Pa (20Pa~2090m³/h)
4E-350 220V/50Hz 0~90Pa (20Pa~1960m³/h)
4E-350 120V/60Hz 0~90Pa (20Pa~2440m³/h)
6D-350 380V/50Hz 0~60Pa (20Pa~1170m³/h)
6E-350 220V/50Hz 0~60Pa (20Pa~1240m³/h)
6E-350 120V/60Hz 0~60Pa (20Pa~1156m³/h)



			VOLTAGE 额定电压 V	FREQUENCY 频率 Hz	CURRENT 额定电流 A	INPUT 输入功率 W	SPEED 额定转速 r/min	AIR VOLUME 额定风量 m³/h	CAPACITANCE 电容 μF	NOISE 噪音 dBA	NET WEIGHT 净重 kg	LICENSE 证书	NO. ON THE CURVE
YWF-4D-350-S-102/34-G	YWF-4D-350-S-102/34-T	YWF-4D-350-S-102/34-B	380	50	0.38	140	1380	2290	/	62	5.0		1
YWF-4E-350-S-102/34-G	YWF-4E-350-S-102/34-T	YWF-4E-350-S-102/34-B	220	50	0.65	140	1380	2270	4	62	5.0		2
			120	60	1.65	180	1600	2580	16	62	5.0		3
YWF-6D-350-S-102/34-G	YWF-6D-350-S-102/34-T	YWF-6D-350-S-102/34-B	380	50	0.30	80	920	1520	/	56	5.0		4
YWF-6E-350-S-102/34-G	YWF-6E-350-S-102/34-T	YWF-6E-350-S-102/34-B	220	50	0.40	80	920	1590	3	56	5.0		5
			120	60	0.68	80	1080	1840	8	56	5.0		6

