Product Information

Direct Acting Solenoid Valve, DN 10 Media Separated

Series 01.010.124



A.u.K. Müller

Solenoid valves
Control valves
Special valves and systems

A.u.K. Müller GmbH & Co. KG
Dresdener Str. 162
D-40595 Düsseldorf/Germany

Tel.: +49(0)211-7391-0
Fax: +49(0)211-7391-281

e-mail: info@akmueller.de
Internet: www.akmueller.de

Characteristics

- Direct acting
- Normally closed (NC)
- Internal plunger assembly medium separated
- Low pressure range of up to 60 mbar
- Solenoid replaceable while medium circuit remains untouched, solenoid rotatable 4 x 90°
- Suitable for hot water up to 98°C
- Long term performance capability
- High operating safety by the use of high quality materials and 100% final testing of the products

Description

This 2/2-way solenoid valve has a 10 mm orifice and is designed for use with potable water and physically and chemically similar media. It is suitable for use in low pressure applications such as controlling flow from a tank and can handle a maximum pressure head of 60 cm.

The valve is direct acting in operation, normally closed (NC) and the coil system is separated from the medium.

These valves have a single body chamber. Coils are available in all common voltage and frequency ranges.

The electrical operational safety is guaranteed by the electrical insulation coordination, which corresponds to the VDE 110 regulations. The manufacturing process includes a 100% electrical safety test in accordance with the VDE 0631 Part 1000 regulations.

The use of high quality insulation materials enables a 100 % duty cycle is be achieved, even at high medium temperatures. For example, the valve body is reinforced with glass fibre to enable use with hot water. Protection against corrosion of inner parts exposed to the medium is achieved by a separating membrane.

Applications

- Dosing systems
- Low pressure applications
- Cleaning equipment
- Industrial appliances


Approvals

Approved versions available on request:

KTW - BWGL

- KTW-BWGL
- Others on request

Typical Performance Curve
(measured under laboratory conditions)




© copyright A.u.K. Müller, technical changes reserved


Direct Acting Solenoid Valve, DN 10
Media Separated

A.u.K. Müller

Series 01.010.124



1) Fixing groove



Technical Data

Type	solenoid valve	
Construction	2/2-way single chamber straight valve, direct acting	
Function	NC (normally closed)	
Fitting position	coil upwardly	
Media	cold and heated potable water and physically and chemically similar media	
T-Medium	5 - 98	°C
T-Ambient	5 - 50	°C
DN	10	mm
p-Operating	0 - 60	mbar
Coil type	MS 06, MS 24, MS 25	
Nominal voltages	220 - 240 120 42 24 24	V AC 50-60 Hz V AC 50-60 Hz V AC 50 Hz V AC 50/60 Hz V DC
	other voltages on request	
Voltage tolerance	+10% -15%	
Duty cycle	100%	
Nominal power	8,5 W	13 VA (AC only)
Protection Type	see coils	
Coil connections	flat tabs 6,3 x 0,8 mm plug socket according to EN 175301-803 (IP65), several cable connections (IP68)	
Insulation class	F	according to EN 60730
Protection class	see coils	according to EN 60730

Materials

Valve body	PA 66 glass fibre reinforced PPE on request PEI on request
Plunger guide	stainless steel
Plunger and spring	stainless steel
Membrane and sealings	VMQ EPDM on request
Coil coating	PBT,PET or epoxy resin
Filter (inlet)	stainless steel POM on request

Coils

		MS 06	MS 24	MS 25
Protection Type according to ISO 206653 / DIN EN 60529		**IP 00**	**IP 65**	**IP 65 / 68**
Protection class DIN EN 61140 / DIN EN 60730	**I** with protective conductor system		-	-
	II with reinforced insulation			
	III for SELV or PELV			

 © copyright A.u.K. Müller, technical changes reserved

Series 01.010.124

Options

Material	Inlet		Outlet		Length	Height	Depth
	Ø A	A1	Ø B	B1	L	H	T
PA 66	G 3/4	20,0	14,5 nozzle	17,0	82,0	72,0	35,0
PA 66	G 3/4	20,0	11,5 nozzle	17,0	82,0	72,0	35,0
PA 66	G 3/4	20,0	14,5 nozzle inner Ø 10	17,0	82,0	72,0	35,0
PPE	G 3/4	20,0	14,5 nozzle	17,0	82,0	72,0	35,0
PA 66	G 3/4	20,0	1/8 NPT female	------	65,0	72,0	35,0
PA 66	G 3/4	20,0	G 1/4	12,0	77,0	72,0	35,0
PA 66	G 3/4	20,0	G 1/8 x 10 inner	-------	65,0	72,0	35,0
PEI	G 3/4	20,0	14,5 nozzle	17,0	82,0	72,0	35,0
PA 66	.75-11.5 NH	20,0	11,5 nozzle	17,0	82,0	72,0	35,0
PPE	3/4 - 14 NPT	20,0	11,5 nozzle	17,0	82,0	72,0	35,0
PPE	.75-11.5 NH	20,0	14,5 nozzle	17,0	82,0	72,0	35,0

© copyright A.u.K. Müller, technical changes reserved