Product Information

Dispense valve, DN 14

Series 40.014.111



Description

2/2-way solenoid valve of nominal diameter DN 12 for liquid dispense. This valve is direct controlled and normally closed (NC).

Valves of this design are medium separated seat valves, where the plunger is separated by a diaphragm from the medium. The valve seat is made of scale build up inhibiting PTFE.

This valve can be manufactured with a variety of customised connections in DC or AC voltage. Low power or PPM triggering can be used.

Electrical operating safety is achieved by PBT coating of the coil and can be supported by an additional protection circuit.

The valve is available in different PSU valve body types and is distinguished primarily by its food grade and hot water capability.

Applications


- hot / cold drink dispensers
- tank or boiler draining
- automatic animal feeding equipment

Possible approvals

Approved versions available on request:

- NSF 169
- WRAS
- KTW/W270
- UL
- Others on request

typical performance curve



A.u.K. Müller

Solenoid valves
Control valves
Special valves and systems

A.u.K. Müller GmbH & Co. KG
Dresdener Str. 162
D-40595 Düsseldorf/Germany

Tel.: +49(0)211-7391-0
Fax: +49(0)211-7391-281

e-mail: info@akmueller.de
Internet: www.akmueller.de

Characteristics


- direct controlled
- plunger separated by diaphragm from medium
- PTFE valve seat to inhibit scale build up
- long term performance capability
- suitable for food and hot water appliances
- works from zero pressure
- similar hydraulic performance for AC or DC types
- other hydraulic connections on request
- complete drainage of valve outlet after shut off
- easy to assemble and service
- coil change without opening of medium circuit, coil can be mounted 4 x 90°
- high operating safety through the use of high quality and 100% final testing of the products

© copyright A.u.K. Müller, technical changes reserved

Dispense valve, DN 14

A.u.K. Müller

Series 40.014.111



Technical Data

Type	dispense valve	
Construction	2/2-way single chamber valve inlet ninety degree to the outlet, direct acting	
Function	NC (normally closed)	
Fitting position	coil pointing upwards	
Media	cold and heated potable water and physically and chemically similar media	
T-Medium	98	°C max.
T-Ambient	70	°C max.
DN	14	mm
p-Operating	0 - 60	mbar
Coil type	MS.006, MS.024, MS.025	
Nominal voltages	230 110 24 24	V AC 50/60 Hz V AC 50/60 Hz V AC 50/60 Hz V DC
	other voltages on request	
Voltage tolerance	+10% -15%	
Duty cycle	50% (30 s on/30 s off)	
Nominal power	9,5 W	16,4 VA (AC only)
Protection type	IP 00	higher IP-classes on request
Coil connection	flat tabs 6,3 x 0,8 mm (others on request)	
Insulation class	F	according to EN 60730
Protection class	I	according to EN 60730 (for incorporation in class I)

Materials

Valve body	PSU
Valve seat	PTFE
Plunger guide	stainless steel
Plunger	stainless steel
Membrane and sealings	VMQ
Coil coating	PBT, PET or epoxi resin

Valve body version

~000

Options


1)	Ventilation of outlet nozzle to drain downstream tubing completely. Different lengths of breather tube on request.
2)	Boiler sealings on request

MS.006 (IP00)	
MS.024 (IP65)	
MS.025 (IP67, IP68)	


© copyright A.u.K. Müller, technical changes reserved

Series 40.014.111

Alternative valve body with G 1/2 inlet thread




Valve body version **~001**



© copyright A.u.K. Müller, technical changes reserved

Series 40.014.111

Tank sealings material: VMQ



For valve body version	ID.	
~000	005000	 Seal for tank inlet nipples

E1017 © copyright A.u.K. Müller, technical changes reserved